


		Class	Weight
1	Cover according to standart EN124 (☒)	A35 (3,5 t) ☐	13 kg
		B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
2	Maintenance shaft (☒)	800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
		1500...1750 ☐	52 kg
		1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
		2250...2500 ☐	80 kg
3	Ladder		
4	Storage capacity for grease	450 l	
5	Grease separation chamber	1920 l	
6	Sludge trap	710 l	
7	Grease level alarm sensor (☒)	☐	
		Nominal flow rate	7 l/s
		Total capacity	2620 l
		Weight excluding manhole shaft/lid	166/250 kg

Product <b>Greasly</b>	Name <b>Grease separator Greasly 7 B</b>		Scale <b>1:25</b>	
Design by <b>V.Laucius</b>	Checked by <b>E.Mozuraitis</b>	Approved by <b>E.Kuodis</b>		Drawing type <b>Customer drawing</b>
 <b>UAB ENEKA</b> Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Construction site <b>-</b>	Drawing no. <b>-</b>	
		Date <b>12/9/2021</b>	Lang. <b>en</b>	Sheet <b>1</b>