



		Class	Weight
1	Cover according to standart EN124 (☒)	A35 (3,5 t) □	13 kg
		B125 (12,5 t) □	45 kg
		C250 (25 t) □	55 kg
		D400 (40 t) □	90 kg
2	Maintenance shaft (☒)	800...1000 □	31 kg
		1000...1250 □	33 kg
		1250...1500 □	42 kg
		1500...1750 □	52 kg
		1750...2000 □	62 kg
		2000...2250 □	71 kg
		2250...2500 □	80 kg
3	Ladder		
4	Storage capacity for grease	640 l	
5	Grease separation chamber	2730 l	
6	Sludge trap	1030 l	
7	Grease level alarm sensor (☒)	□	
		Nominal flow rate	10 l/s
		Total capacity	3760 l
		Weight excluding manhole shaft/lid	206/317 kg

Product Greasly	Name Grease separator Greasly 10		Scale 1:25	
Design by V.Laucius	Checked by E.Mozuraitis	Approved by E.Kuodis		Drawing type Customer drawing
 UAB ENEKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Construction site	Drawing no.	
		-	-	-
		Date	Lang.	Sheet
		12/9/2021	en	1